



## FEATURES

- ◆ Bright color-rich picture
- ◆ Anti-glare protective coating
- ◆ Lightweight durable construction
- ◆ Simple to install and set-up
- ◆ Touch and navigate
- ◆ Wide range of compatibility
- ◆ Annotate and capture screens
- ◆ Compatible with all Windows platforms

## PRODUCT OVERVIEW

Turn your large format display into an interactive experience by simply attaching this screen overlay over the front of your plasma or LCD flat panel monitor.

Set-up and connection is fast and easy.

Touch the screen and experience the immediacy and excitement of navigating through windows or multimedia programs. Applications are limitless, ranging from conference room collaboration to public information kiosks. Also, because the overlay is a lightweight slim-fit design, in keeping with the overall look and feel of your flat panel display you barely notice it.

### Bright color-rich picture

Less than 15% light loss with excellent viewing angle.

### Anti-glare protective coating

Ideal in most ambient environments with scratch resistant screen surface.

### Lightweight durable construction

Only adds 25 mm to the outside edge of plasma display.

### Simple to install and set-up

No special skills or training required, connects to PC serial port.

### Touch and navigate

Move through windows applications, point and click, emulates right mouse button.

### Wide range of compatibility

Attaches over the front most plasma & LCD models from leading brands.

### Annotate and capture screens

Capture and save notes using Presentation Tools interactive software

Compatible with all Windows platforms. Runs with any PC applications under Windows 9x, NT, 2000, XP

# TS-RM SPECIFICATIONS

Construction	Aluminium, mild steel, safety glass
Bezel color	Gun metal grey, optional colors available
Luminous transmission	85% +/- 2% ASTM D1003
Viewing angle	160 degrees
Aspect ratio	16:9
Operating voltage	5 volts DC (70mA typical)
Power supply	Power tap from keyboard/mouse port
Communications	RS232 serial port, 9600 baud
Touchscreen type	Resistive membrane
Touch membrane	175 microns
Touch activation force	50 grams nominal
Linearity	Less than +/- 1% error
Touch durability	5 million touches in single location
Operating temperature	0 to 50 degrees C
Operating humidity	Up to 90% non-condensing

## Applications:

- Customer retail sites
- Passenger terminals
- Information Kiosks
- Gaming and entertainment
- Exhibitions & conferences
- Process control and plant monitoring
- Video conferencing & collaboration
- Multimedia Presentations
- Business review meetings

## COMPATIBILITY

Screen overlays are compatible with plasma and LCD models from the following brands.


Eizo	Fujitsu	Hantarex	Hitachi
JVC	LG	NEC	NEC/Mitsubishi
Panasonic	Pioneer	Sanyo	Samsung
Sharp	Sony	Toshiba	Zentih

## What's included:

- Interactive touchscreen overlay
- Controller interface
- Connecting cables
- Mounting brackets
- Touchscreen drivers
- Presentation Tools

## MINIMUM REQUIREMENTS

- Pentium or higher PC
- 128 MB RAM
- Windows 95 or higher
- 10 MB free hard disk space
- Spare serial COM port
- PS/2 mouse/keyboard port



... "add a little zap to your presentation."™



**Boeckeler Instruments, Inc.**

4650 S. Butterfield Drive • Tucson, Arizona 85714 USA

Phone: 520.745.0001 • Fax: 520.745.0004 • E-mail: info@boeckeler.com • www.pointmaker.com

© 2008 Boeckeler Instruments, Inc. Boeckeler is a registered trademark of Boeckeler Instruments, Inc., Tucson, Arizona. All other trademarks are the property of their respective owners. All specifications subject to change without notice.